



KLIPSCH SOLUTIONS CATALOG MSRP

January 2009



C O N T E N T S

In-Ceiling Loudspeakers

THX® Series	4
7000 Series	
CDT™ Series	4
5000 Series	
3000 Series	
2000 Series	
In-Ceiling Speakers	6
2000 Series	
1000 Series	
Dual Tweeter Speakers	7
2000 Series	
1000 Series	
Surround Speakers	8
7000 Series	
Subwoofers	9
5000 Series	
Subwoofer Amplifier	

In-Wall Loudspeakers

LCR Speakers	10
7000 Series	
6000 Series	
5000 Series	
2000 Series	
In-Wall Speakers	11
5000 Series	
3000 Series	
2000 Series	
1000 Series	
Surround Speakers	13
7000 Series	
5000 Series	
Subwoofers	13
5000 Series	
Subwoofer Amplifier	

Outdoor

AW Series	14
Full-Range Speakers	
Summed-Mono Speaker	
Subwoofer	
Rock Speaker	

Accessories

Installation Kits	16
Fire-Rated Enclosures	16

THX® Ultra2 System

System Components	18
Architectural Speakers	19

Reference Series

Reference Speakers	21
Powered Subwoofers	26
RSX Satellite Series	28
Concert Series	29

Icon Series

Icon X	30
Icon W	32

Heritage Series

Klipschorn	35
La Scala II	35
Cornwall III	35
Heresy III	35

Headphones

Image	36
Custom	37

Additional Accessories

Accessories	38
-----------------------	----

Discreet but not understated, Klipsch's extensive line of high-end, easy-to-install in-ceiling speakers offer dynamic performances and outstanding reliability. Perfect for home theater or stereo music applications, these architectural models deliver powerful and detailed sound without sonic compromises that plague competing designs. All Klipsch in-ceiling products have paintable frames and grilles so they can match any décor.



In-Ceiling Loudspeakers

THX® Series

KL-7502-THX |

7000 Series



Frequency Response	45Hz-20kHz ± 3dB
Power Handling	100W continuous / 400W peak
Rec. Amplifier Power	150W
Sensitivity	93dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
High Frequency Drivers	1" (2.5cm) Titanium diaphragm compression driver mated to 60° x 90° x 110° VCT variable coverage technology skewed horn
HF X-over Freq	1800Hz & 1200Hz
Low Frequency Drivers	Dual 5.25" (13.3cm) high-output, Cerametallic™ cone woofers
Dimensions	15.25" (38.7cm) dia
Cutout Dimensions	13.25" (33.7cm) dia
Mounting Depth	9.5" (24.1cm)
Weight	12 lbs. (5.4kg)
Installation Kit	IK-502-C (sold seperately)
Fire Rated Enclosure	Not Available

MSRP
\$999 EA

Shipping quantity: Single
Shipping weight: lbs.
UPC Code:



In-Ceiling CDT™ Series

CDT-5800-C |

5000 Series



Frequency Response	49Hz-20kHz ± 3dB
Sensitivity	94dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) titanium dome compression tweeter with a swiveling 100° Tractrix® Horn and one 8" (20.3cm) pivoting aluminum cone woofer
Weight	7.4 lbs. (3.4kg)
Dimensions	11" (27.9cm) Cutout: 9.8" (24.8cm)
Installation Kit	IK-800-C (sold separately)
Fire Rated Enclosure	ME-800-C (sold separately)

MSRP
\$399 EA

Shipping quantity: Single
Shipping weight: 8.5 lbs.
UPC Code: 743878016499



CDT-5650-C |



Frequency Response	60Hz-20kHz ± 3dB
Sensitivity	95dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) titanium dome compression tweeter with a swiveling 100° Tractrix Horn and one 6.5" (16.5cm) pivoting aluminum cone woofer
Weight	7 lbs. (3.2kg)
Dimensions	9.5" (24.1cm) Cutout: 8.3" (21cm)
Installation Kit	IK-650-C (sold separately)
Fire Rated Enclosure	ME-650-C (sold separately)

MSRP
\$349 EA

Shipping quantity: Single
Shipping weight: 8 lbs.
UPC Code: 743878016482



3000 Series

CDT-3800-C |



Frequency Response	56Hz-20kHz ± 3dB
Sensitivity	92dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) aluminum dome compression tweeter with a swiveling Tractrix Horn and one 8" (20.3cm) pivoting IMG cone woofer
Weight	7.3 lbs. (3.3kg)
Dimensions	11" (27.9cm) Cutout: 9.8" (24.8cm)
Installation Kit	IK-800-C (sold separately)
Fire Rated Enclosure	ME-800-C (sold separately)

MSRP
\$349 EA

Shipping quantity: Single
Shipping weight: 8.4 lbs.
UPC Code: 743878016475



CDT-3650-C |



Frequency Response	63Hz-20kHz ± 3dB
Sensitivity	93dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) aluminum dome compression tweeter with a swiveling Tractrix Horn and one 6.5" (16.5cm) pivoting IMG cone woofer
Weight	6.8 lbs. (3.1kg)
Dimensions	9.5" (24.1cm) Cutout: 8.3" (21cm)
Installation Kit	IK-650-C (sold separately)
Fire Rated Enclosure	ME-650-C (sold separately)

MSRP
\$299 EA

Shipping quantity: Single
Shipping weight: 8 lbs.
UPC Code: 743878016468



2000 Series


CDT-2800-C |



Frequency Response	65Hz-20kHz ± 3dB
Sensitivity	93dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) silk dome tweeter with a swiveling Tractrix Horn and one 8" (20.3cm) pivoting poly woofer
Weight	7.1 lbs. (3.2kg)
Dimensions	11" (27.9cm) Cutout: 9.8" (24.9cm)
Installation Kit	IK-800-C (sold separately)
Fire Rated Enclosure	ME-800-C (sold separately)

MSRP
\$249 EA

Shipping quantity: Single
Shipping weight: 8.2 lbs.
UPC Code: 743878016451



CDT-2650-C |



Frequency Response	77Hz-20kHz ± 3dB
Sensitivity	91dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) silk dome tweeter with a swiveling Tractrix Horn and one 6.5" (16.5cm) pivoting poly woofer
Weight	6.6 lbs. (3.0kg)
Dimensions	9.5" (24.1cm) Cutout: 8.3" (21cm)
Installation Kit	IK-650-C (sold separately)
Fire Rated Enclosure	ME-650-C (sold separately)

MSRP
\$229 EA

Shipping quantity: Single
Shipping weight: 7.8 lbs.
UPC Code: 743878016444



In-Ceiling Speakers

2000 Series

R-2800-C



Frequency Response	65Hz-20kHz ± 3dB
Sensitivity	93dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) silk dome tweeter and one 8" (20.3cm) poly woofer
Weight	7.6 lbs. (3.5kg)
Dimensions	11" (27.9cm) Cutout: 9.8" (24.9cm)
Installation Kit	IK-800-C (sold separately)
Fire Rated Enclosure	ME-800-C (sold separately)

MSRP
\$229 EA

Shipping quantity: Single
Shipping weight: 8.5 lbs.
UPC Code: 743878016512



R-2650-C



Frequency Response	77Hz-20kHz ± 3dB
Sensitivity	91dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) silk dome tweeter and one 6.5" (16.5cm) poly woofer
Weight	7 lbs. (3.2kg)
Dimensions	9.5" (24.1cm) Cutout: 8.3" (21cm)
Installation Kit	IK-650-C (sold separately)
Fire Rated Enclosure	ME-650-C (sold separately)

MSRP
\$199 EA

Shipping quantity: Single
Shipping weight: 8 lbs.
UPC Code: 743878016505



1000 Series

R-1800-C



Frequency Response	56Hz-20kHz ± 3dB
Sensitivity	89dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	35 watts (140 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) polymer dome, liquid-cooled tweeter and one 8" (20.3cm) poly woofer
Weight	5.8 lbs. (2.6kg)
Dimensions	11" (27.9cm) Cutout: 9.8" (24.9cm)
Installation Kit	IK-800-C (sold separately)
Fire Rated Enclosure	ME-800-C (sold separately)

MSRP
\$129 EA

Shipping quantity: Single
Shipping weight: 6.4 lbs.
UPC Code: 743878018530

R-1650-C



Frequency Response	57Hz-20kHz ± 3dB
Sensitivity	91dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	35 watts (140 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) polymer dome, liquid-cooled tweeter and one 6.5" (16.5cm) poly woofer
Weight	5.1 lbs. (2.3kg)
Dimensions	9.5" (24.1cm) Cutout: 8.3" (21cm)
Installation Kit	IK-650-C (sold separately)
Fire Rated Enclosure	ME-650-C (sold separately)

MSRP
\$119 EA

Shipping quantity: Single
Shipping weight: 5.7 lbs.
UPC Code: 743878018516



Weatherized



Bass Control



Treble Control



Pivoting Woofer



Swiveling Tweeter

Dual Tweeter Speakers

2000 Series

R-2800-CSM |



Frequency Response	65Hz-20kHz ± 3dB
Sensitivity	93dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using dual .75" (1.9cm) silk dome tweeters and one 8" (20.3cm) poly woofer
Weight	7.9 lbs. (3.6kg)
Dimensions	11" (27.9cm) Cutout: 9.8" (24.9cm)
Installation Kit	IK-800-C (sold separately)
Fire Rated Enclosure	ME-800-C (sold separately)

MSRP
\$299 EA

Shipping quantity: Single
Shipping weight: 8.5 lbs.
UPC Code: 743878016437



R-2650-CSM |



Frequency Response	79Hz-20kHz ± 3dB
Sensitivity	92dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using dual .75" (1.9cm) silk dome tweeters and one 6.5" (16.5cm) poly woofer
Weight	7.2 lbs. (3.3kg)
Dimensions	9.5" (24.1cm) Cutout: 8.3" (21cm)
Installation Kit	IK-650-C (sold separately)
Fire Rated Enclosure	ME-650-C (sold separately)

MSRP
\$249 EA

Shipping quantity: Single
Shipping weight: 8 lbs.
UPC Code: 743878016420



1000 Series

R-1650-CSM |



Frequency Response	50Hz-20kHz ± 3dB
Sensitivity	87dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	35 watts (140 watts peak)
Drive Components	Two-way system using dual .5" (1.3cm) polymer dome liquid-cooled tweeters and one 6.5" (16.5cm) poly woofer
Weight	5.3 lbs. (2.4kg)
Dimensions	9.5" (24.1cm) Cutout: 8.3" (21cm)
Installation Kit	IK-650-C (sold separately)
Fire Rated Enclosure	ME-650-C (sold separately)

MSRP
\$169 EA

Shipping quantity: Single
Shipping weight: 6 lbs.
UPC Code: 743878018523

Surround Speakers

KS-7502-THX |

7000 Series



Frequency Response	45Hz-20kHz ± 3dB
Power Handling	60W continuous / 240W peak
Rec. Amplifier Power	110W
Sensitivity	93dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
High Frequency Drivers	Dual 1" (2.5cm) Titanium diaphragm compression drivers mated to WDST™ Tractrix® Horn Array
HF X-over Freq	2500Hz
Low Frequency Drivers	Dual 5.25" (13.3cm) high-output, Cerametallic™ cone woofers
Dimensions	15.25" (38.7cm) dia
Cutout Dimensions	13.25" (33.7cm) dia
Mounting Depth	9.5" (24.1cm)
Weight	11 lbs. (5kg)
Installation Kit	IK-502-C (sold seperately)
Fire Rated Enclosure	Not Available

MSRP
\$999 EA

Shipping quantity: Single
Shipping weight: lbs.
UPC Code:



 Weatherized	 Bass Control	 Treble Control	 Pivoting Woofer	 Swiveling Tweeter
---	--	--	---	---

Subwoofers

RW-5101-C |

In-Ceiling Subwoofer



Frequency Response	35-120kHz ± 4dB
Sensitivity	91dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
Amplifier	Use only with RSA-500
Amplifier Power	See RSA-500 Specifications
Low Frequency Drivers	10" (25.4cm) Cerametallic™ cone woofer
Dimensions	15.25" (38.7cm) dia
Cutout Dimensions	13.25" (33.7cm) dia
Mounting Depth	9.5" (24.1cm)
Weight	13 lbs. (6kg)
Installation Kit	IK-502-C (sold seperately)
Fire Rated Enclosure	Not Available

MSRP
\$599 EA

Shipping quantity: Single
Shipping weight: lbs.
UPC Code:

RSA-500 |

Subwoofer Amplifier



Amplifier Type	Bash Digital Hybrid
Amplifier Power	FTC Rated Power: 500 watts continuous into 4 ohms @ <2% THD Dynamic Power: 1000 watts
Front Controls	Volume and Variable Crossover
Rear Controls	Phase Switch (0/180), EQ Selector, Trigger Input, Power Mode Selector, Main Power Switch
Inputs	L/R and LFE Line-level RCA jacks L/R High-level speaker binding posts
Outputs	L/R and LFE Line-level RCA jacks (unfiltered) L/R speaker binding posts
Weight	17.5 lbs. (7.9kg)
Dimensions	3.5" (8.9cm) H x 16.8" (42.7cm) W
Dimensions With Feet	3.8" (9.6cm) H x 16.8" (42.7cm) W
Voltage	110/120 VAC 60Hz
Finish	Black Anodized Brushed Aluminum
Accessories	Rack Ears (included) *For use only with RW-5802, RW-5101, AW-800-SW, or IC-8T-SW

MSRP
\$799 EA

Shipping quantity: Single
Shipping weight: 21 lbs.
UPC Code: 743878017311

LCR Speakers

7000 Series

KL-7800-THX |



Frequency Response	80Hz-20kHz ± 3dB
Sensitivity	91dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
Power Handling	150 watts (600 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) titanium dome compression driver with an 80° x 80° Tractrix Horn and one 8" (20.3cm) aluminum cone woofer
Weight	17.5 lbs. (7.9kg)
Dimensions	20.8" (52.7cm) H x 11.8" (29.8cm) W Cutout: 19" (48.3cm) H x 10" (25.4cm) W
Enclosure	Sealed: MDF baffle, ABS shell
Installation Kit	IK-802-W (sold separately)
Fire Rated Enclosure	Not Available

MSRP
\$1100 EA

Shipping quantity: Single
Shipping weight: 20 lbs.
UPC Code: 743878017281



6000 Series

KL-6504-THX |



Frequency Response	46Hz-20kHz ± 3dB
Power Handling	150W continuous / 600W peak
Rec. Amplifier Power	200W
Sensitivity	92dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
High Frequency Drivers	1" (2.5cm) Titanium diaphragm compression driver mated to 90° x 90° square Tractrix® Horn
HF X-over Freq	2100Hz & 250Hz
Low Frequency Drivers	Four 5.25" (13.3cm) high-output, fiberglass cone woofers
Dimensions	28.5" (72.4cm) H x 8" (20.3cm) W
Cutout Dimensions	27.25" (69.2cm) H x 6.5" (16.5cm) W
Mounting Depth	3.75" (9.5cm)
Weight	18.3 lbs. (8.3kg)
Installation Kit	IK-504-W (sold separately)
Fire Rated Enclosure	Not Available

MSRP
\$749 EA

Shipping quantity: Single
Shipping weight: lbs.
UPC Code:



6000 Series

KL-6502-THX |



Frequency Response	46Hz-20kHz ± 3dB
Power Handling	100W continuous / 400W peak
Rec. Amplifier Power	150W
Sensitivity	92dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
High Frequency Drivers	1" (2.5cm) Titanium diaphragm compression driver mated to 90° x 90° square Tractrix® Horn
HF X-over Freq	2100Hz & 1200Hz
Low Frequency Drivers	Dual 5.25" (13.3cm) high-output, fiberglass cone woofers
Dimensions	17.75" (45.1cm) H x 8" (20.3cm) W
Cutout Dimensions	16.5" (41.9cm) H x 6.5" (16.5cm) W
Mounting Depth	3.75" (9.5cm)
Weight	9.6 lbs. (4.4kg)
Installation Kit	IK-502-W (sold separately)
Fire Rated Enclosure	Not Available

MSRP
\$499 EA

Shipping quantity: Single
Shipping weight: lbs.
UPC Code:



R-5502-W |

5000 Series



Frequency Response	46Hz-20kHz ± 3dB
Power Handling	75W continuous / 300W peak
Rec. Amplifier Power	130W
Sensitivity	92dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
High Frequency Drivers	1" (2.5cm) Titanium diaphragm compression driver mated to pivoting 90° x 90° square Tractrix® Horn
HF X-over Freq	2200Hz & 1300Hz
Low Frequency Drivers	Dual 5.25" (13.3cm) Cerametallic™ cone woofers
Dimensions	17.75" (45.1cm) H x 8" (20.3cm) W
Cutout Dimensions	16.5" (41.9cm) H x 6.5" (16.5cm) W
Mounting Depth	3.5" (8.9cm)
Weight	6.5 lbs. (2.9kg)
Installation Kit	IK-502-W (sold separately)
Fire Rated Enclosure	Not Available

MSRP
\$399 EA

Shipping quantity: Single
Shipping weight: lbs.
UPC Code:

R-2502-W |

2000 Series



Frequency Response	47Hz-20kHz ± 3dB
Power Handling	60W continuous / 240W peak
Rec. Amplifier Power	110W
Sensitivity	91dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
High Frequency Drivers	1" (2.5cm) Silk dome tweeter
HF X-over Freq	2200Hz
Low Frequency Drivers	Dual 5.25" (13.3cm) polypropylene cone woofers
Dimensions	17.75" (45.1cm) H x 8" (20.3cm) W
Cutout Dimensions	16.5" (41.9cm) H x 6.5" (16.5cm) W
Mounting Depth	3.5" (8.9cm)
Weight	6.25 lbs. (2.8kg)
Installation Kit	IK-502-W (sold separately)
Fire Rated Enclosure	Not Available

MSRP
\$299 EA

Shipping quantity: Single
Shipping weight: lbs.
UPC Code:

In-Wall Speakers

R-5800-W |

5000 Series



Frequency Response	40Hz-20kHz ± 3dB
Sensitivity	94dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) titanium dome compression tweeter with a swiveling 90° x 60° Tractrix Horn and one 8" (20.3cm) aluminum cone woofer
Weight	7.9 lbs. (3.6kg)
Dimensions	16.1" (40.9cm) H x 10.6" (26.9cm) W
Cutout Dimensions	14.8" (37.6cm) H x 9.3" (23.6cm) W
Installation Kit	IK-800-W (sold separately)
Fire Rated Enclosure	Not Available

MSRP
\$399 EA

Shipping quantity: Single
Shipping weight: 9 lbs.
UPC Code: 743878016222



R-5650-W |



Frequency Response	52Hz-20kHz ± 3dB
Sensitivity	93dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) titanium dome compression tweeter with a swiveling 90° x 60° Tractrix Horn and one 6.5" (16.5cm) aluminum cone woofer
Weight	7.2 lbs. (3.3kg)
Dimensions	14.3" (36.3cm) H x 9.3" (23.6cm) W Cutout: 13" (33cm) H x 8" (20.3cm) W
Installation Kit	IK-650-W (sold separately)
Fire Rated Enclosure	ME-650-W (sold separately)

MSRP
\$349 EA

Shipping quantity: Single
Shipping weight: 8 lbs.
UPC Code: 743878016208



3000 Series

R-3800-W |



Frequency Response	46Hz-20kHz ± 3dB
Sensitivity	93dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) aluminum dome compression tweeter with a swiveling 90° x 60° Tractrix Horn and one 8" (20.3cm) IMG cone woofer
Weight	7.9 lbs. (3.6kg)
Dimensions	16.1" (40.9cm) H x 10.6" (26.9cm) W Cutout: 14.8" (37.6cm) H x 9.3" (23.6cm) W
Installation Kit	IK-800-W (sold separately)
Fire Rated Enclosure	Not Available

MSRP
\$349 EA

Shipping quantity: Single
Shipping weight: 9 lbs.
UPC Code: 743878016215




R-3650-W |



Frequency Response	60Hz-20kHz ± 3dB
Sensitivity	92dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) aluminum dome compression tweeter with a swiveling 90° x 60° Tractrix Horn and one 6.5" (16.5cm) IMG cone woofer
Weight	7.2 lbs. (3.3kg)
Dimensions	14.3" (36.3cm) H x 9.3" (23.6cm) W Cutout: 13" (33cm) H x 8" (20.3cm) W
Installation Kit	IK-650-W (sold separately)
Fire Rated Enclosure	ME-650-W (sold separately)

MSRP
\$299 EA

Shipping quantity: Single
Shipping weight: 8 lbs.
UPC Code: 743878016192



2000 Series

R-2650-W |



Frequency Response	65Hz-20kHz ± 3dB
Sensitivity	91dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) silk dome tweeter and one 6.5" (16.5cm) poly cone woofer
Weight	7.2 lbs. (3.3kg)
Dimensions	14.3" (36.3cm) H x 9.3" (23.6cm) W Cutout: 13" (33cm) H x 8" (20.3cm) W
Installation Kit	IK-650-W (sold separately)
Fire Rated Enclosure	ME-650-W (sold separately)

MSRP
\$199 EA

Shipping quantity: Single
Shipping weight: 8 lbs.
UPC Code: 743878016185



Weatherized



Bass Control



Treble Control



Pivoting Woofer



Swiveling Tweeter

1000 Series

R-1650-W |



Frequency Response	53Hz-20kHz ± 3dB
Sensitivity	88dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	30 watts (120 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) polymer dome, liquid-cooled tweeter and one 6.5" (16.5cm) poly woofer
Weight	6.5 lbs. (3kg)
Dimensions	14.3" (36.3cm) H x 9.3" (23.6cm) W Cutout: 13" (33cm) H x 8" (20.3cm) W
Installation Kit	IK-650-W (sold separately)
Fire Rated Enclosure	ME-650-W (sold separately)

MSRP
\$129 EA

Shipping quantity: Single
Shipping weight: 7.5 lbs.
UPC Code: 743878018547

Surround Speakers

7000 Series

KS-7800-THX |



Frequency Response	80Hz-20kHz ± 3dB
Sensitivity	90dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	100 watts (400 watts peak)
Drive Components	Two-way system using dual 1" (2.5cm) titanium dome compression drivers with WDST™ engineered Tractrix Horns and one 8" (20.3cm) aluminum cone woofer
Weight	17 lbs. (7.7kg)
Dimensions	20.8" (52.7cm) H x 11.8" (29.8cm) W Cutout: 19" (48.3cm) H x 10" (25.4cm) W
Enclosure	Sealed: MDF baffle, ABS shell
Installation Kit	IK-802-W (sold separately)
Fire Rated Enclosure	Not Available

MSRP
\$800 EA

Shipping quantity: Single
Shipping weight: 20 lbs.
UPC Code: 743878017281



5000 Series

R-5650-S |



Frequency Response	52Hz-20kHz ± 3dB
Sensitivity	93dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using dual 1" (2.5cm) titanium dome compression tweeters with WDST™ engineered Tractrix Horns and one 6.5" (16.5cm) aluminum cone woofer
Weight	7.2 lbs. (3.3kg)
Dimensions	14.3" (36.3cm) H x 9.3" (23.6cm) W Cutout: 13" (33cm) H x 8" (20.3cm) W
Installation Kit	IK-650-W (sold separately)
Fire Rated Enclosure	ME-650-W (sold separately)

MSRP
\$379 EA

Shipping quantity: Single
Shipping weight: 8 lbs.
UPC Code: 743878016185

Subwoofers

In-Wall Subwoofer

RW-5802 |



Frequency Response	41-140Hz ± 3dB
Maximum Output	106dB @ 30Hz 1/8 space, 1 meter
Drive Components	Two 8" (20.3cm) Cerametallic front-firing woofers
Amplifier Type	Use with RSA-500
Amplifier Power	See RSA-500
Controls	See RSA-500
Inputs	Gold plated binding posts
Enclosure	Sealed: MDF baffle, ABS shell
Weight	21.1 lbs. (9.6kg)
Dimensions	20.8" (52.8cm) H x 11.8" (29.9cm) W Cutout: 19" (48.3cm) H x 10" (25.4cm) W

MSRP
\$549 EA

Shipping quantity: Single
Shipping weight: 24 lbs.
UPC Code: 743878017304

RSA-500 (amplifier) |

See page 9.

Full-Range Speakers

AW Series

AW-650 |



Frequency Response	70Hz-20kHz ± 3dB
Sensitivity	95dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	85 watts (340 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) titanium dome tweeter with a 90° x 90° Tractrix Horn and one 6.5" (16.5cm) IMG cone woofer
Weight	9 lbs. (4.1kg)
Dimensions	15" (38.1cm) H x 9.5" (24.1cm) W x 11" (27.9cm) D
Finish	White & Black

MSRP
\$549 PR

Shipping quantity: Pair
Shipping weight: 26 lbs.
UPC Code: 743878015218



AW-525 |



Frequency Response	80Hz-20kHz ± 3dB
Sensitivity	94dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	75 watts (300 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) titanium dome tweeter with a 90° x 90° Tractrix Horn and one 5.25" (13.3cm) IMG cone woofer
Weight	6.5 lbs. (3kg)
Dimensions	11.8" (30cm) H x 8" (20.3cm) W x 9" (22.9cm) D
Finish	White & Black

MSRP
\$449 PR

Shipping quantity: Pair
Shipping weight: 18 lbs.
UPC Code: 743878015195



AW-500 |



Frequency Response	95Hz-20kHz ± 3dB
Sensitivity	92dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	65 watts (260 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) polymer dome tweeter with a 90° x 90° Tractrix Horn and one 5" (12.7cm) IMG cone woofer
Weight	6 lbs. (2.7kg)
Dimensions	11.8" (30cm) H x 8" (20.3cm) W x 9" (22.9cm) D
Finish	White

MSRP
\$349 PR

Shipping quantity: Pair
Shipping weight: 17 lbs.
UPC Code: 743878015171



AW-400 |



Frequency Response	91Hz-20kHz ± 3dB
Sensitivity	91dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Drive Components	Two-way system using one 1" (2.5cm) polymer dome tweeter with a 90° x 90° Tractrix Horn and one 4" (10.2cm) IMG cone woofer
Weight	5 lbs. (2.3kg)
Dimensions	9.5" (24.1cm) H x 6.5" (16.5cm) W x 7.8" (19.8cm) D
Finish	White

MSRP
\$249 PR

Shipping quantity: Pair
Shipping weight: 12 lbs.
UPC Code: 743878015164



Weatherized	Bass Control	Treble Control	Pivoting Woofer	Swiveling Tweeter
-------------	--------------	----------------	-----------------	-------------------

Summed-Mono Speaker

AW-500-SM |



Frequency Response	80Hz-20kHz ± 3dB
Sensitivity	94dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak) total
Drive Components	Two-way system using dual 1" (2.5cm) polymer dome tweeters with dual 90°x 90° Tractrix Horns and one 5" (12.7cm) IMG cone woofer
Weight	9.5 lbs. (4.3kg)
Dimensions	8.3" (21.1cm) H x 16" (40.6cm) W x 11" (27.9cm) D
Finish	White

MSRP
\$399 EA

Shipping quantity: Single
Shipping weight: 12 lbs.
UPC Code: 743878015225



Subwoofer

AW-800-SW |



Frequency Response	51-135Hz ± 4dB
Sensitivity	94dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	150 watts (600 watts peak)
Drive Components	Subwoofer system using one 8" (20.3cm) IMG cone, front-firing woofer
Amplifier Type	Use with RSA-500 (See page 11)
Crossover	150Hz internal low-pass and 150Hz high-pass outputs
Weight	19 lbs. (8.6kg)
Dimensions	11.1" (28.3cm) H x 16.4" (41.7cm) W x 11.8" (30cm) D
Finish	White

MSRP
\$449 EA

Shipping quantity: Single
Shipping weight: 23 lbs.
UPC Code: 743878015232



Rock Speakers

AWR-650-SM |



Frequency Response	66Hz-20kHz ±3dB
Sensitivity	94dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
Power Handling	50 watts continuous (200W peak)
Drive Components	Two 0.75" poly dome tweeters using Neodymium magnets mounted in a plastic housing and a 6.5" poly cone dual voice coil woofer using a ceramic motor and plastic basket.
Amplifier Type	
Crossover	2500Hz
Weight	13 lbs (5.9kg)
Dimensions	17" (43.2cm) H x 15" (38.1cm) W x 11" (27.9cm) D
Finish	Painted: Red, Granite, Sandstone

MSRP
\$299 EA

Shipping quantity: Single
Shipping weight: 13 lbs lbs.
UPC Code:



Accessories

Installation Kits

IK-802-W	The Klipsch IK-802-W installation kit offers increased mounting flexibility for our THX Ultra2 in-wall speakers and in-wall subwoofer. UPC Code: 743878018592	Shipping quantity: Pair Shipping weight: 3 lbs.	MSRP OPEN
IK-800-C	The Klipsch IK-800-C installation kit offers increased mounting flexibility for all of our round in-ceiling speakers that employ an 8-inch woofer. UPC Code: 743878015416	Shipping quantity: Pair Shipping weight: 2 lbs.	MSRP OPEN
IK-650-C	The Klipsch IK-650-C installation kit offers increased mounting flexibility for all of our round in-ceiling speakers that employ a 6.5-inch woofer. UPC Code: 743878015409	Shipping quantity: Pair Shipping weight: 2 lbs.	MSRP OPEN
IK-800-W	The Klipsch IK-800-W installation kit offers increased mounting flexibility for all of our in-wall speakers that employ an 8-inch woofer (excluding RW-5802 and THX). UPC Code: 743878015393	Shipping quantity: Pair Shipping weight: 2 lbs.	MSRP OPEN
IK-650-W	The Klipsch IK-650-W installation kit offers increased mounting flexibility for all of our in-wall speakers that employ a 6.5-inch woofer (excluding CS Series). UPC Code: 743878015386	Shipping quantity: Pair Shipping weight: 2 lbs.	MSRP OPEN
IK-502-W	The Klipsch IK-502-W installation kit offers increased mounting flexibility for our in-wall LCR speakers (R-2502-W, R-5502-W, KL-6502-THX). UPC Code: 743878020434	Shipping quantity: Each Shipping weight: 2 lbs.	MSRP OPEN
IK-504-W	The Klipsch IK-504-W installation kit offers increased mounting flexibility for our in-wall speakers (KL-6504-THX). UPC Code: N/A	Shipping quantity: Each Shipping weight: 2 lbs.	MSRP OPEN
IK-502-C	The Klipsch IK-502-C installation kit offers increased mounting flexibility for our THX Ultra2 in-ceiling speakers as well as the RW-5101-C in-ceiling subwoofer (KL-7502-THX, KS-7502-THX). UPC Code: 743878020458	Shipping quantity: Each Shipping weight: 2 lbs.	MSRP OPEN

Fire-Rated Enclosures

ME-800-C		Fits all 8-inch round in-ceiling models. UPC Code: 743878017274	MSRP OPEN
Designed to meet UL2043 requirements for installation in plenum spaces Tested to comply with: UL 263 · ASTM E119-98 · NFPA 251 · UBC 7-1 · ULC CAN/ULC-S101 -M89		Shipping quantity: Single Shipping weight: 9.2 lbs.	
ME-650-C		Fits all 6.5-inch round in-ceiling models. UPC Code: 743878017267	MSRP OPEN
Designed to meet UL2043 requirements for installation in plenum spaces Tested to comply with: UL 263 · ASTM E119-98 · NFPA 251 · UBC 7-1 · ULC CAN/ULC-S101 -M89		Shipping quantity: Single Shipping weight: 9.2 lbs	
ME-650-W		Fits all 6.5-inch in-wall models (excluding Contractor Series). UPC Code: 743878017250	MSRP OPEN
Designed to meet UL2043 requirements for installation in plenum spaces Tested to comply with: UL 263 · ASTM E119-98 · NFPA 251 · UBC 7-1 · ULC CAN/ULC-S101 -M89		Shipping quantity: Single Shipping weight: 7.7 lbs	

Utilizing the same professional-grade technology as our renowned commercial theater systems, every Klipsch THX® Ultra2 speaker brings real cinema sound to the comforts of home. Expertly delivering the raw explosiveness and fine detail of any film format, these products, which can be assembled in a variety of combinations, will forever shatter your expectations for home theater performance.



THX® Ultra2 System

LCR Speakers

KL-650-THX |



Frequency Response	48Hz-20kHz ± 3dB
Sensitivity	97dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Crossover	1400Hz
Power Handling	150 watts maximum continuous (600 watts peak)
Enclosure Type	Bass reflex via front-firing port
Enclosure Material	Medium density fiberboard (MDF)
Tweeter	1" (2.5cm) magnetically shielded, titanium-dome compression driver with 9.6 oz ceramic magnet structure.
High-Frequency Horn	10" x 6" rectangular 90° x 60° Tractrix Horn
Woofer	Two 6.5" (16.5cm) magnetically shielded, Cerametallic cone, cast aluminum frame drivers
Input Connections	Two sets of binding post speaker terminals (connected via bass strap jumpers)
Dimensions	15" (38.1cm) H x 17" (43.2cm) W x 12.5" (31.8cm) w/grille D
Weight	39 lbs. (17.7kg)
Finish	Galaxy Black cabinet with black anodized aluminum fascia
Mounting	4-bolt pattern 1/4"-20 threaded inserts

MSRP
\$1300 EA

Shipping quantity: Single
Shipping weight: 42 lbs.
UPC Code:
74387801465 (left)
74387801466 (right)

KL-525-THX |



Frequency Response	80Hz-20kHz ± 3dB
Sensitivity	94dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Crossover	1500Hz
Power Handling	100 watts maximum continuous (400 watts peak)
Enclosure Type	Sealed
Enclosure Material	Medium density fiberboard (MDF)
Tweeter	1" (2.5cm) magnetically shielded, titanium-dome compression driver with 9.6 oz ceramic magnet structure.
High-Frequency Horn	10" x 6" rectangular 90° x 60° Tractrix Horn
Woofer	Two 5.25" (13.3cm) magnetically shielded, Cerametallic cone, cast aluminum frame drivers
Input Connections	Two sets of binding post speaker terminals (connected via bass strap jumpers)
Dimensions	12.75" (32.4cm) H x 16" (40.6cm) W x 12.5" (31.8cm) w/grille D
Weight	32 lbs. (14.5kg)
Finish	Galaxy Black cabinet with black anodized aluminum fascia
Mounting	4-bolt pattern 1/4"-20 threaded inserts

MSRP
\$1100 EA

Shipping quantity: Single
Shipping weight: 43 lbs.
UPC Code: 74387801467

Surround Speakers

KS-525-THX |



Frequency Response	80Hz-20kHz ± 3dB
Sensitivity	96dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Crossover	2100Hz
Power Handling	100 watts maximum continuous (400 watts peak)
Enclosure Type	Sealed
Enclosure Material	Medium density fiberboard (MDF)
Tweeter	Two 1" (2.5cm) magnetically shielded, titanium-dome compression driver with 9.6 oz ceramic magnet structure.
High-Frequency Horn	5" square 90° x 60° Tractrix Horn
Woofer	Two 5.25" (13.3cm) magnetically shielded, Cerametallic cone, cast aluminum frame drivers
Input Connections	Two sets of binding post speaker terminals (connected via bass strap jumpers)
Dimensions	13.75" (35cm) H x 13" (33cm) W x 8.5" (21.6cm) D
Weight	20 lbs. (9.1kg)
Finish	Galaxy Black cabinet with black anodized aluminum fascia
Mounting	Dual keyholes and 2-bolt pattern 1/4"-20 threaded inserts

MSRP
\$1300 PR

Shipping quantity: Single
Shipping weight: 43 lbs.
UPC Code: 74387801468

Subwoofer

KW-120-THX |



Frequency Response	20Hz-200Hz ± 3dB
Max. Acoustic Output	130dB @ 30Hz, 122dB @ 20Hz, 112dB@ 15Hz 1/8 space, 1M (2 enclosures side-by-side per THX Ultra2)
Impedance	8 ohms compatible
Enclosure Type	Bass reflex via front-firing port
Enclosure Material	Medium density fiberboard (MDF)
Amplifier	Use only with KA-1000-THX
Woofer	12" (30.5cm) front-firing, Cerametallic cone, cast aluminum frame drivers with a 240oz ceramic magnet structure
Input	1 Speakon NL2 jack and included cable
Dimensions	20.25" (51.4cm) H x 17.75" (45.1cm) W x 17.75" (31.8cm) w/grille D
Weight	80 lbs. (36.3kg)
Finish	Galaxy Black cabinet with black anodized aluminum fascia

MSRP
\$1300 EA

Shipping quantity: Single
Shipping weight: 93 lbs.
UPC Code: 74387801469

Amplifier

KA-1000-THX |



Frequency Response	20Hz-1kHz +0/-3dB
Amplifier	High-Efficiency Class D
Amplifier Power	FTC Rated Power: 500W into 8 ohms, 1000W into 4 ohms, 20Hz-1kHz @ <1.5% THD Dynamic Power: 2050W into 8 ohms, 3025W into 4 ohms @ 5% THD
Auto Power On	2 second ON delay, 15 minute off delay
Low Pass Crossover	Continuously variable from 40Hz-120Hz, 24dB/octave slope above 120z (non-THX mode)
Inputs	2 Gold-plated RCA phono jacks
Outputs	2 Gold-plated RCA phono jacks (unfiltered) 2 Speakon® NL2 jacks
Phase	Continuously variable from 0° to 180°
Dimensions	4.75" (12.1cm) H x 17.5" (44.5cm) W x 12.25" (31.1cm) D
Weight	27 lbs. (12.3kg)
Finish	Black anodized aluminum
Voltage	110/120 VAC 60Hz
Export Voltage	230 VAC 50/60Hz
Features	THX On/Off Boundary Gain Compensation On/Off * For use only with KW-120-THX (supports 1 or 2 subwoofers)

MSRP
\$1500 EA

Shipping quantity: Single
Shipping weight: 31 lbs.
UPC Code: 74387801470

In-Wall & In-Ceiling |

THX® Ultra2 Architectural



KL-7800-THX

For full specs, see page 10.



KS-7800-THX

For full specs, see page 12.



KL-7502-THX

For full specs, see page 4.



KS-7502-THX

For full specs, see page 8.

The best-selling loudspeakers in America keep getting better. The new Reference IV Series is led by five all new wood veneer flagship models that bring the power, detail and emotion of the acclaimed RF-7 system into attractive, slim cabinets designed to complement today's high-performance flat-screen video displays. In addition to the evolutionary upgrades found throughout the rest of the line, our WDST™ surrounds are all new with a second woofer added for greater output and dynamics and a smaller enclosure size that looks great on the wall. Add the finishing touch with a complete line of compact high-output subwoofers featuring a revolutionary new digital user-interface. With best-of-class performance, stylish good looks and the best support in the industry, the Klipsch Reference Series isn't just your most profitable speaker line - it's The Ultimate Sound Experience.™



Reference Series

Floorstanding Speakers

RF-83 |



Frequency Response	29Hz-21kHz ± 3dB
Sensitivity	100dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	250 watts (1000 watts peak)
Crossover	1650Hz
Drive Components	Two-way system using one 1.25" (3.18cm) titanium dome compression driver and three 8" (20.3cm) Cerametallic® woofers
Weight	100 lbs. (45.4kg)
Height	49" (124.5cm)
Width	9.25" (23.5cm)
Depth	20.5" (52cm)
Finish	Black Ash or Cherry wood veneer

MSRP
\$1399 EA

Shipping quantity: Single
Shipping weight: 107 lbs.
UPC Code: 743878016277 (Black)
UPC Code: 743878016864 (Cherry)

RF-63 |



Frequency Response	30Hz-21kHz ± 3dB
Sensitivity	99dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	175 watts (700 watts peak)
Crossover	1700Hz
Drive Components	Two-way system using one 1.25" (3.18cm) titanium dome compression driver and three 6.5" (16.5cm) Cerametallic® woofers
Weight	81 lbs. (36.8kg)
Height	45.5" (115.6cm)
Width	8.5" (21.6cm)
Depth	19.5" (49.5cm)
Finish	Black Ash or Cherry wood veneer

MSRP
\$999 EA

Shipping quantity: Single
Shipping weight: 86.5 lbs.
UPC Code: 743878016291 (Black)
UPC Code: 743878016888 (Cherry)

RF-82 |



Frequency Response	33Hz-23kHz ± 3dB
Sensitivity	98dB @ 2.83V/1 meter
Nominal Impedance	8 ohms
Power Handling	150 watts (600 watts peak)
Crossover	2000Hz
Drive Components	Two-way system using one 1" (2.54cm) titanium dome compression driver and two 8" (20.3cm) Cerametallic® woofers
Weight	66 lbs. (30kg)
Height	43" (109.2cm)
Width	9.5" (24.1cm)
Depth	16.25" (41.3cm)
Finish	Black woodgrain vinyl

MSRP
\$549 EA

Shipping quantity: Single
Shipping weight: 70.5 lbs.
UPC Code: 743878016284 (Black)
UPC Code: 743878016871 (Cherry)

RF-62 |



Frequency Response	38Hz-23kHz ± 3dB
Sensitivity	97dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	125 watts (500 watts peak)
Crossover	1800Hz
Drive Components	Two-way system using one 1" (2.54cm) titanium dome compression driver and two 6.5" (16.5cm) Cerametallic® woofers
Weight	54 lbs. (24.5kg)
Height	40" (101.6cm)
Width	8.5" (21.6cm)
Depth	15.5" (39.4cm)
Finish	Black woodgrain vinyl

MSRP
\$439 EA

Shipping quantity: Single
Shipping weight: 58 lbs.
UPC Code: 743878016406 (Black)

RF-52 |



Frequency Response	34Hz-23kHz ± 3dB
Sensitivity	96dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	100 watts (400 watts peak)
Crossover	1900Hz
Drive Components	Two-way system using one 1" (2.54cm) titanium dome compression driver and two 5.25" (13.3cm) Cerametallic® woofers
Weight	38 lbs. (17.3kg)
Height	37" (94cm)
Width	6.75" (17.1cm)
Depth	14.25" (36.2cm)
Finish	Black woodgrain vinyl

MSRP
\$329 EA

Shipping quantity: Single
Shipping weight: 41 lbs.
UPC Code: 743878016307 (Black)

RF-10 |



Frequency Response	59Hz-20kHz ± 3dB
Sensitivity	95dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	75 watts (300 watts peak)
Crossover	2280Hz
Drive Components	Two-way system using one 1" (2.54cm) titanium dome compression driver and two 4.5" (11.4cm) Cerametallic® woofers
Weight	36 lbs. (15.9kg)
Height	34" (86.4cm)
Width	6.75" (17.1cm)
Depth	10" (25.4cm)
Finish	Black woodgrain vinyl

MSRP
\$269 EA

Shipping quantity: Single
Shipping weight: 38.5 lbs.
UPC Code: 743878014914 (Black)

Bookshelf Speakers

RB-81 |



Frequency Response	46Hz-23kHz ± 3dB
Sensitivity	97dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	150 watts (600 watts peak)
Crossover	1800Hz
Drive Components	Two-way system using one 1" (2.54cm) titanium dome compression driver and one 8" (20.3cm) Cerametallic® woofer
Weight	30 lbs. (13.6kg)
Height	19" (48.3cm)
Width	9.25" (23.5cm)
Depth	12.25" (31.1cm)
Finish	Black woodgrain vinyl

MSRP
\$399 EA

Shipping quantity: Single
Shipping weight: 32 lbs.
UPC Code: 743878016314 (Black)
UPC Code: 743878016895 (Cherry)

RB-61 |



Frequency Response	43Hz-23kHz ± 3dB
Sensitivity	95dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	100 watts (400 watts peak)
Crossover	2000Hz
Drive Components	Two-way system using one 1" (2.54cm) titanium dome compression driver and one 6.5" (16.5cm) Cerametallic® woofer
Weight	22 lbs. (10kg)
Height	15.4" (39.1cm)
Width	8.5" (21.6cm)
Depth	12.25" (31.1cm)
Finish	Black woodgrain vinyl

MSRP
\$499 PR

Shipping quantity: Single
Shipping weight: 23.5 lbs.
UPC Code: 743878016321 (Black)
UPC Code: 743878016901 (Cherry)

RB-51 |



Frequency Response	50Hz-23kHz ± 3dB
Sensitivity	92dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	75 watts (300 watts peak)
Crossover	2000Hz
Drive Components	Two-way system using one 1" (2.54cm) titanium dome compression driver and one 5.25" (13.3cm) Cerametallic® woofer
Weight	12 lbs. (5.5kg)
Height	11.4" (29cm)
Width	6.5" (16.5cm)
Depth	10.75" (27.3cm)
Finish	Black woodgrain vinyl

MSRP
\$389 PR

Shipping quantity: Pairs
Shipping weight: 13 lbs.
UPC Code: 743878016338 (Black)

RB-10 |



Frequency Response	90Hz-20kHz ± 3dB
Sensitivity	90dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Crossover	2800Hz
Drive Components	Two-way system using one 1" (2.54cm) titanium dome compression driver and one 4" (10.2cm) Cerametallic® woofer
Weight	6 lbs. (2.7kg)
Height	8.7" (22.1cm)
Width	5.6" (14.1cm)
Depth	7.8" (19.8cm)
Finish	Black woodgrain vinyl

MSRP
\$269 PR

Shipping quantity: Pairs
Shipping weight: 6.5 lbs.
UPC Code: 743878014921 (Black)

Center Channels

RC-64 |



Frequency Response	62Hz-21kHz ± 3dB
Sensitivity	99dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	200 watts (800 watts peak)
Crossover	1150Hz, 1800Hz
Drive Components	Tapered-array system using one 1.25" (3.18cm) titanium dome compression driver and four 6.5" (16.5cm) Cerametallic® woofers
Weight	66 lbs. (30kg)
Height	8" (20.3cm)
Width	33" (83.3cm)
Depth	13.5" (34.3cm)
Finish	Black Ash or Cherry wood veneer

MSRP
\$999 EA

Shipping quantity: Single
Shipping weight: 70.5 lbs.
UPC Code: 743878016345 (Black)
UPC Code: 743878016925 (Cherry)

RC-62 |



Frequency Response	57Hz-23kHz ± 3dB
Sensitivity	98dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	150 watts (600 watts peak)
Crossover	1150Hz, 1650Hz
Drive Components	Tapered-array system using one 1" (2.54cm) titanium dome compression driver and two 6.5" (16.5cm) Cerametallic® woofers
Weight	32 lbs. (14.5kg)
Height	8" (20.3cm)
Width	23.5" (59.7cm)
Depth	12.5" (31.8cm)
Finish	Black woodgrain vinyl

MSRP
\$499 EA

Shipping quantity: Single
Shipping weight: 32.5 lbs.
UPC Code: 743878016352 (Black)
UPC Code: 743878016925 (Cherry)

RC-52 |



Frequency Response	67Hz-23kHz ± 3dB
Sensitivity	96dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	150 watts (600 watts peak)
Crossover	1400Hz, 1600Hz
Drive Components	Tapered-array system using one 1" (2.54cm) titanium dome compression driver and two 5.25" (16.5cm) Cerametallic® woofers
Weight	22 lbs. (10kg)
Height	6.75" (17.1cm)
Width	20.5" (52cm)
Depth	10.5" (26.7cm)
Finish	Black woodgrain vinyl

MSRP
\$329 EA

Shipping quantity: Single
Shipping weight: 23.5 lbs.
UPC Code: 743878016369 (Black)

RC-10 |



Frequency Response	88Hz-23kHz ± 3dB
Sensitivity	95dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	75 watts (300 watts peak)
Crossover	2550Hz
Drive Components	Tapered-array system using one 1" (2.54cm) titanium dome compression driver and two 4" (10.2cm) Cerametallic® woofers
Weight	13 lbs. (5.9kg)
Height	5.4" (13.7cm)
Width	16" (40.6cm)
Depth	9.1" (23.1cm)
Finish	Black woodgrain vinyl

MSRP
\$219 EA

Shipping quantity: Single
Shipping weight: 14 lbs.
UPC Code: 743878014938 (Black)

Surround Speakers

RS-62



Frequency Response	50Hz-23kHz ± 3dB
Sensitivity	97dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	150 watts (600 watts peak)
Crossover	2000Hz
Drive Components	Two-way WDST® system using two 1" (2.54cm) titanium dome compression drivers and two 6.5" (16.5cm) Cerametallic® woofers
Weight	28 lbs. (12.7kg)
Height	15" (38.1cm)
Width	14.75" (37.5cm)
Depth	9.75" (24.8cm)
Finish	Matte black

MSRP
\$549 EA

Shipping quantity: Single
Shipping weight: 30 lbs.
UPC Code: 743878012415 (Black)

RS-52



Frequency Response	62Hz-23kHz ± 3dB
Sensitivity	95dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	100 watts (400 watts peak)
Crossover	1700Hz
Drive Components	Two-way WDST® system using two 1" (2.54cm) titanium dome compression drivers and two 5.25" (13.3cm) Cerametallic® woofers
Weight	10 lbs. (4.5kg)
Height	10" (25.4cm)
Width	10.75" (27.3cm)
Depth	10.5" (26.7cm)
Finish	Matte black

MSRP
\$389 EA

Shipping quantity: Single
Shipping weight: 11 lbs.
UPC Code: 743878016383 (Black)

RS-42



Frequency Response	52Hz-23kHz ± 3dB
Sensitivity	93dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	75 watts (300 watts peak)
Crossover	1700Hz
Drive Components	Two-way WDST® system using two 1" (2.54cm) titanium dome compression drivers and two 4" (10.2cm) Cerametallic® woofers
Weight	10 lbs. (4.5kg)
Height	10" (25.4cm)
Width	10.75" (27.3cm)
Depth	10.5" (26.7cm)
Finish	Matte black

MSRP
\$249 EA

Shipping quantity: Single
Shipping weight: 11 lbs.
UPC Code: 743878016390 (Black)

RS-10



Frequency Response	82Hz-20kHz ± 3dB
Sensitivity	91dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	50 watts (200 watts peak)
Crossover	2000Hz
Drive Components	Two-way WDST® system using two 1" (2.54cm) titanium dome compression drivers and one 4" (10.2cm) Cerametallic® woofer
Weight	5 lbs. (2.3kg)
Height	5.8" (14.6cm)
Width	12.8" (32.5cm)
Depth	5.8" (14.6cm)
Finish	Matte black

MSRP
\$159 EA

Shipping quantity: Single
Shipping weight: 5.5 lbs.
UPC Code: 743878014945 (Black)

Powered Subwoofers

RT-12d |



Frequency Response	19-120Hz ± 3dB
Maximum Output	120dB @ 30Hz 1/8 space, 1 meter
Drive Components	One 12" (30.5cm) active Cerametallic front-firing woofer and two 12" (30.5cm) Cerametallic rear-firing passive radiators
Amplifier Type	Bash Digital Hybrid
Amplifier Power	FTC Rated Power: 800 watts continuous @<2% THD Dynamic Power: 2000 watts
Controls	DCS control and feature set w/5 system presets and ARC™ Adaptive Room Correction
Inputs	L/R Line-level RCA jacks, calibration Microphone, USB 2.0
Outputs	L/R Line-level RCA jacks (passthru)
Weight	71 lbs. (32.2kg)
Dimensions	18.75" (47.6cm) H x 24" (61cm) W x 21.75" (55.2cm) D
Voltage	110/120 VAC 60Hz
Finish	Cherry or Black Ash wood veneer

MSRP
\$2199 EA

Shipping quantity: Single
Shipping weight: 76 lbs.
UPC Code: 743878017533 (Black)
UPC Code: 743878017564 (Cherry)

RT-10d |



Frequency Response	22-120Hz ± 3dB
Maximum Output	119dB @ 30Hz 1/8 space, 1 meter
Drive Components	One 10" (25.4cm) active Cerametallic front-firing woofer and two 10" (25.4cm) Cerametallic rear-firing passive radiators
Amplifier Type	Bash Digital Hybrid
Amplifier Power	FTC Rated Power: 700 watts continuous @<2% THD Dynamic Power: 1500 watts
Controls	DCS control and feature set w/5 system presets and ARC™ Adaptive Room Correction
Inputs	L/R Line-level RCA jacks, calibration Microphone, USB 2.0
Outputs	L/R Line-level RCA jacks (passthru)
Weight	58 lbs. (26.3kg)
Dimensions	15.8" (40.1cm) H x 20.5" (52.1cm) W x 18.75" (47.6cm) D
Voltage	110/120 VAC 60Hz
Finish	Cherry or Black Ash wood veneer

MSRP
\$1799 EA

Shipping quantity: Single
Shipping weight: 62 lbs.
UPC Code: 743878017472 (Black)
UPC Code: 743878017502 (Cherry)

RSW-10d |



Frequency Response	24-120Hz ± 3dB
Maximum Output	114dB @ 30Hz 1/8 space, 1 meter
Drive Components	One 10" (25.4cm) active Cerametallic rear-firing woofer and one 10" (25.4cm) Cerametallic front-firing passive radiator
Amplifier Type	Bash Digital Hybrid
Amplifier Power	FTC Rated Power: 500 watts continuous @<2% THD Dynamic Power: 1200 watts
Controls	DCS control and feature set w/3 system presets
Inputs	L/R Line-level RCA jacks
Outputs	-
Weight	45 lbs. (20.4kg)
Dimensions	13.75" (34.9cm) H x 12.75" (32.4cm) W x 17.5" (44.5cm) D
Voltage	110/120 VAC 60Hz
Finish	Black Ash woodgrain vinyl

MSRP
\$1299 EA

Shipping quantity: Single
Shipping weight: 48 lbs.
UPC Code: 743878017410 (Black)
UPC Code: 743878017441 (Cherry)

RW-12d |



Frequency Response	24-120Hz ± 3dB
Maximum Output	116dB @ 30Hz 1/8 space, 1 meter
Drive Components	One 12" (30.5cm) Cerametallic front-firing woofer
Amplifier Type	Bash Digital Hybrid
Amplifier Power	FTC Rated Power: 350 watts continuous @<2% THD Dynamic Power: 825 watts
Controls	DCS control and feature set w/3 system presets
Inputs	L/R Line-level RCA jacks L/R High-level speaker binding posts
Outputs	-
Weight	49 lbs. (22.2kg)
Dimensions	19.2" (48.8cm) H x 14.6" (37.1cm) W x 21" (53.3cm) D
Voltage	110/120 VAC 60Hz
Finish	Black Ash woodgrain vinyl

MSRP
\$799 EA

Shipping quantity: Single
Shipping weight: 52.5 lbs.
UPC Code: 743878017380 (Black)

RW-10d |



Frequency Response	28-120Hz ± 3dB
Maximum Output	112dB @ 30Hz 1/8 space, 1 meter
Drive Components	One 10" (25.4cm) Cerametallic front-firing woofer
Amplifier Type	Bash Digital Hybrid
Amplifier Power	FTC Rated Power: 260 watts continuous @<2% THD Dynamic Power: 575 watts
Controls	DCS control and feature set w/3 system presets
Inputs	L/R Line-level RCA jacks L/R High-level speaker binding posts
Outputs	-
Weight	39 lbs. (17.7kg)
Dimensions	17.8" (45.2cm) H x 12.5" (31.8cm) W x 19" (48.3cm) D
Voltage	110/120 VAC 60Hz
Finish	Black Ash woodgrain

MSRP
\$549 EA

Shipping quantity: Single
Shipping weight: 42 lbs.
UPC Code: 743878017359 (Black)

RPW-10 |



Frequency Response	35-120Hz ± 3dB
Maximum Output	110dB @ 30Hz 1/8 space, 1 meter
Drive Components	One 10" (25.4cm) Fiber composite front-firing woofer
Amplifier Type	Bash Digital Hybrid
Amplifier Power	FTC Rated Power: 200 watts continuous @<2% THD Dynamic Power: 420 watts
Controls	Volume, Lowpass, Phase, Auto Power
Inputs	L/R Line-level RCA jacks L/R High-level speaker binding posts
Outputs	-
Weight	31 lbs. (14.1kg)
Dimensions	15.75" (40cm) H x 11.5" (39.2cm) W x 17.75" (45.1cm) D
Voltage	110/120 VAC 60Hz
Finish	Matte Black vinyl

MSRP
\$389 EA

Shipping quantity: Single
Shipping weight: 33 lbs.
UPC Code: 743878017328 (Black)

RSX Series

RSX-5



Frequency Response	92Hz-20kHz ± 3dB
Sensitivity	93dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Crossover	2000Hz
Power Handling	75 watts (300 watts peak)
Enclosure	Bass-reflex via rear-firing port
Drive Components	Two-way system using one 1" (2.5cm) magnetically shielded, titanium dome compression driver tweeter with an integral round 90° Tractrix Horn and one 5.25" (13.3cm) magnetically shielded, Cerametallic cone woofer
Weight	7 lbs. (3.2kg)
Height	12.3" (31.2cm) including base
Width	6.75" (17.1cm)
Depth	9.4" (24cm)
Finish	Black
Mounting	Base swivels 360° for on-wall mounting via keyholes

MSRP
\$209 EA

Shipping quantity: Single
Shipping weight: 7.5 lbs.
UPC Code: 743878014495 (Black)
UPC Code: 743878014501 (Silver)

RSX-4



Frequency Response	92Hz-20kHz ± 3dB
Sensitivity	90dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Crossover	2300Hz
Power Handling	50 watts (200 watts peak)
Enclosure	Bass-reflex via rear-firing port
Drive Components	Two-way system using one 1" (2.5cm) magnetically shielded, titanium dome compression driver with an integral round 90° Tractrix Horn and one 4" (10.2cm) magnetically shielded, Cerametallic cone woofer
Weight	4.5 lbs. (2kg)
Dimensions	10.2" (26cm) H including base x 5.6" (14.2cm) W x 7.8" (19.8cm) D
Finish	Black
Mounting	Base swivels 360° for on-wall mounting via keyholes

MSRP
\$159 EA

Shipping quantity: Single
Shipping weight: 5 lbs.
UPC Code: 743878014471 (Black)
UPC Code: 743878014488 (Silver)
UPC Code: 743878015492 (White)

RSX-3 System



Frequency Response	116Hz-20kHz ± 3dB
Sensitivity	89dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Crossover	2740Hz
Power Handling	40 watts (160 watts peak)
Enclosure	Bass-reflex via rear-firing port
Drive Components	Two-way system using one .75" (1.8cm) magnetically shielded, titanium dome compression driver with an integral round 90° Tractrix Horn and one 3.5" (8.9cm) magnetically shielded, Cerametallic cone woofer
Weight	4.4 lbs. (2kg)
Dimensions	8.75" (22.2cm) H including base x 4.8" (12.2cm) W x 6.7" (17cm) D
Finish	Black
Mounting	Base swivels 360° for on-wall mounting via keyholes

MSRP
\$699 SYSTEM

Shipping quantity: 4 bundled with 1 RCX-3 (Cinema 6)
Shipping weight: 25.5 lbs.
UPC Code: 743878014891 (Black)
UPC Code: 743878014907 (Silver)

RCX-4 |



Frequency Response	92Hz-20kHz ± 3dB
Sensitivity	94dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Crossover	2100Hz
Power Handling	75 watts (300 watts peak)
Enclosure	Bass-reflex via dual rear-firing ports
Drive Components	Tapered Array system using one 1" (2.5cm) magnetically shielded, titanium dome compression driver with an integral round 90° Tractrix Horn and two 4" (10.2cm) magnetically shielded, Cerametallic cone woofers
Weight	7.5 lbs. (3.4kg)
Dimensions	7.5" (19cm) H including base x 14.8" (37.6cm) W x 8.4" (21.3cm) D
Finish	Black
Mounting	Base swivels 360° for on-wall mounting via keyholes

MSRP
\$259 EA

Shipping quantity: Single
Shipping weight: 8 lbs.
UPC Code: 743878014518 (Black)
UPC Code: 743878014525 (Silver)

Concert Series

CS-700 |



Description	2.1 DVD Home Entertainment System, Wireless Subwoofer and 2nd Zone (RoomGroove)
Frequency Response	30 Hz to 20 kHz ± 3dB
Crossover	125 Hz, 24 dB/Octave
Weight	40 lbs. (18.14kg)
Finishes	Controller: Black plastic Satellites: High-gloss piano black plastic Subwoofer: Black MDF

MSRP
\$1299 EA

CS-500 |



Description	2.1 DVD Home Entertainment System
Frequency Response	41 Hz to 20 kHz ± 3dB
Crossover	175 Hz, 24 dB/Octave
Weight	37 lbs.
Finishes	Controller: Black plastic Satellites: High-gloss piano black plastic Subwoofer: Black MDF

MSRP
\$999 EA

RoomGroove |



Description	Compact Wireless iPod® Speaker System
Frequency Response	65 Hz - 17 kHz
Crossover	2.9 kHz
Weight	6 lbs.
Finish	Black with silver accents

MSRP
\$299 EA

Icon X

XB-10 |



Frequency Response	96Hz-23kHz ±3dB
Sensitivity	92dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
Power Handling	50W continuous / 200W peak
Crossover	HF: 2650Hz
Drive Components	0.75" (1.9cm) Titanium diaphragm compression driver mated to 80° x 80° round XT Tractrix® Horn 4" (10.2cm) high-output, fiberglass cone woofer
Weight	6.5 lbs. (2.9kg)
Height	10.8" (27.3cm)
Width	5.75" (14.6cm)
Depth	6" (15.2cm)
Finish	Black anodized w/ high-gloss Black accents

MSRP
\$499 PR

Shipping quantity: Pair
Shipping weight: 15 lbs.
UPC Code: 743878019605

XL-12 |



Frequency Response	94Hz-23kHz ±3dB
Sensitivity	92dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
Power Handling	50W continuous / 200W peak
Crossover	HF: 2650 Hz
Drive Components	0.75" (1.9cm) Titanium diaphragm compression driver mated to 80° x 80° round XT Tractrix® Horn 4" (10.2cm) high-output, fiberglass cone woofer
Weight	7.5 lbs. (3.4kg)
Height	12" (30.5cm)
Width	5.75" (14.6cm)
Depth	6" (15.2cm)
Finish	Black anodized w/ high-gloss Black accents

MSRP
\$299 EA

Shipping quantity: Single
Shipping weight: 9 lbs.
UPC Code: 743878019841

XL-23 |



Frequency Response	86Hz-23kHz ±3dB
Sensitivity	94dB @ 2.83V / 1 meter
Impedance	8 ohms compatible
Power Handling	70W continuous / 275W peak
Crossover	HF: 2500Hz
Drive Components	0.75" (1.9cm) Titanium diaphragm compression driver mated to 80° x 80° round XT Tractrix® Horn Dual 4" (10.2cm) high-output, fiberglass cone woofers
Weight	18 lbs. (8.2kg)
Height	26.3" (66.7cm) including removable table stand
Width	5.75" (14.6cm)
Depth	6" (15.2cm) not including 8" (20.3cm) diameter table stand
Finish	Black anodized w/ high-gloss Black accents

MSRP
\$499 EA

Shipping quantity: Single
Shipping weight: 23 lbs.
UPC Code: 743878019599

XF-48 |



Frequency Response	40Hz-23kHz ±3dB
Amplifier Type	HF: Class A/B, LF: Class D
Amplifier Power	110W continuous system power / 200W peak
Crossover	HF: 2550Hz
Drive Components	0.75" (1.9cm) Titanium diaphragm compression driver mated to 80° x 80° round XT Tractrix® Horn Dual 5.25" (13.3cm) high-output, fiberglass cone woofers with Dual 5.25" x 9" (13.3cm x 22.9cm) passive radiators
Voltage	110/120 VAC 60Hz
Weight	39 lbs. (17.7kg)
Height	48.8" (123.8cm)
Width	7" (17.8cm)
Depth	7.9" (20cm) not including 12" (30.5cm) diameter base
Finish	Black anodized w/ high-gloss Black accents

MSRP
\$1249 EA

Shipping quantity: Single
Shipping weight: 48 lbs.
UPC Code: 743878019582

XW-300d |



Frequency Response	20-120Hz ±3dB
Maximum Output	105dB @ 30Hz 1/8 space, 1 meter
Drive Components	Ultra-high-excursion 8" (20.3cm) fiberglass cone, front-firing woofer
Amplifier Type	BASH® digital hybrid
Amplifier Power	FTC Rated Power: 270 watts continuous @ <2% THD / Dynamic Power*: 480 watts
Inputs	L/R Line-level RCA jacks
Outputs	None
Voltage	110/120 VAC 60Hz
Weight	24 lbs. (10.9kg)
Height	11" (27.9cm)
Width	10" (25.4cm)
Depth	14.25" (36.2cm)
Finish	Black vinyl w/ high-gloss Black accents

MSRP
\$699 EA

Shipping quantity: Single
Shipping weight: 30 lbs.
UPC Code: 743878019872

XW-500d |



Frequency Response	24-120Hz ±3dB
Maximum Output	110dB @ 30Hz 1/8 space, 1 meter
Drive Components	Ultra-high-excursion 10" (25.4cm) fiberglass cone, front-firing woofer
Amplifier Type	BASH® digital hybrid
Amplifier Power	FTC Rated Power: 500 watts continuous @ <2% THD / Dynamic Power*: 1200 watts
Inputs	L/R Line-level RCA jacks
Outputs	None
Voltage	110/120 VAC 60Hz
Weight	48 lbs. (21.8kg)
Height	14" (35.6cm)
Width	13.25" (33.7cm)
Depth	17.5" (44.5cm)
Finish	Black vinyl w/ high-gloss Black accents

MSRP
\$999 EA

Shipping quantity: Single
Shipping weight: 55 lbs.
UPC Code: 743878020472

Icon W

WB-14 |



Frequency Response	87Hz-20kHz ±3dB
Sensitivity	92dB
Impedance	8 ohms
Power Handling	40 W @ 8 ohms
Crossover	HF: 2650Hz
Drive Components	1" (2.5cm) Titanium diaphragm compression driver mated to a 3.75" 80° x 80° round Tractrix® horn; 4.5" (11.4cm) high-output, fiberglass cone woofer
Weight	10 lbs. (4.5kg)
Height	11" (27.9cm)
Width	6.5" (16.5cm)
Depth	6.5" (16.5cm)
Finish	Furniture Grade Wood Veneer available in Cabernet and Espresso

MSRP
\$599 PR

Shipping quantity: Pair
Shipping weight: 18 lbs.
UPC Code: Cabernet 743878020625
Espresso 743878020632

WS-24 |



Frequency Response	93Hz-20kHz ±3dB
Sensitivity	91dB
Impedance	8 ohms
Power Handling	75 W @ 8 ohms
Crossover	2700Hz
Drive Components	Dual 1" (2.5cm) titanium diaphragm compression drivers mated to a 3.75" 80° x 80° Tractrix® Horn; Dual 4.5" (11.4cm) high-output, fiberglass cone woofers
Weight	11 lbs. (4.9kg)
Height	11.5" (29.1cm)
Width	12.75" (32.4 cm)
Depth	7" (17.8cm)
Finish	Furniture Grade Wood Veneer available in Cabernet and Espresso

MSRP
\$375 EA

Shipping quantity: Pair
Shipping weight: 14 lbs.
UPC Code: Cabernet 743878020601
Espresso 743878020618

WC-24 |



Frequency Response	89Hz-20kHz ±3dB
Sensitivity	94.5dB
Impedance	8 ohms
Power Handling	90 W @ 8 ohms
Crossover	2500Hz
Drive Components	1" (2.5cm) titanium diaphragm compression driver mated to a 4.5" 80° x 80° round Tractrix® horn; Dual 4.5" (11.4cm) high-output, fiberglass cone woofers
Weight	11 lbs. (4.9kg)
Height	6.5" (16.5cm)
Width	18" (45.7cm)
Depth	6.5" (16.5cm)
Finish	Furniture Grade Wood Veneer available in Cabernet and Espresso

MSRP
\$599 EA

Shipping quantity: Single
Shipping weight: 15 lbs.
UPC Code: Cabernet 743878020588
Espresso 743878020595

WF-34 |



Frequency Response	57Hz-20kHz ±3dB
Sensitivity	95.5dB
Power Handling	125 W @ 8 ohms
Crossover	2700Hz
Drive Components	1" (2.5cm) titanium diaphragm compression driver mated to a 4.5" 80° x 80° round Tractrix® horn; Triple 4.5" (11.4cm) high-output, fiberglass cone woofers
Enclosure Type	Bass-reflex via dual rear-firing ports
Weight	33 lbs. (14.9kg)
Height	34" (86.4cm)
Width	6.5" (16.5cm)
Depth	9.5" (24.13cm)
Finish	Furniture Grade Wood Veneer available in Cabernet and Espresso

MSRP
\$599 EA

Shipping quantity: Single
Shipping weight: 40 lbs.
UPC Code: Cabernet 743878020540
Espresso 743878020557



Frequency Response	45Hz-20kHz ±3dB
Sensitivity	97dB
Power Handling	150 w @ 8 ohms
Crossover	2500Hz
Drive Components	1" (2.5cm) titanium diaphragm compression driver mated to a 4.5" 80° x 80° round Tractrix® horn; Triple 5.25" (13.3cm) high-output, fiberglass cone woofers
Enclosure Type	Bass-reflex via dual rear-firing ports
Weight	41 lbs. (18.5kg)
Height	43" (109.2cm)
Width	7.25" (18.4cm)
Depth	11.75" (29.8cm)
Finish	Furniture Grade Wood Veneer available in Cabernet and Espresso

MSRP
\$749 EA

Shipping quantity: Single
Shipping weight: 48 lbs.
UPC Code: Cabernet 743878020564
Espresso 743878020571

Among the most popular loudspeakers developed by audio pioneer Paul W. Klipsch, the classic Klipschorn®, La Scala and Heresy were contributors in the birth of the high-fidelity era. Still manufactured and sold around the world today, these legendary Heritage Series products were recently relaunched in honor of the company's 60th anniversary. While the Klipschorn features minor cosmetic and functional revisions, the La Scala II adopts a new finished appearance and the Heresy III offers increased performance through various content upgrades.



Heritage Series

Heritage Series

Klipschorn I



Frequency Response	33Hz-17kHz ± 4dB
Sensitivity	105dB @ 2.83V/1meter
Impedance	8 ohms compatible
Power Handling	100 watts max continuous (400 watts peak)
Crossover	HF: 4500Hz MF: 450Hz
Drive Components	Three-way system using one 1" (2.54cm) Phenolic diaphragm compression driver, one 2" (5.08cm) Phenolic diaphragm compression driver and one 15" Fiber-composite cone/folded horn-loaded
Weight	175 lbs. (79.5kg)
Height	50.75" (128.9cm)
Width	31.25" (79.38cm)
Depth	28.25" (71.75cm)
Finish	Walnut, Cherry or Black Lacquer wood veneer

MSRP
\$4000 EA

Shipping quantity: Single
Shipping weight: 187 lbs.
UPC Code: 743878016833 (Walnut)
UPC Code: 743878017670 (Cherry)
UPC Code: 743878017656 (Black)

La Scala II



Frequency Response	51Hz-17kHz ± 4dB
Sensitivity	105dB @ 2.83V/1 meter
Impedance	8 ohms compatible
Power Handling	100 watts (400 watts peak)
Crossover	HF: 4500Hz MF: 400Hz
Drive Components	Three-way system using one 1" (2.54cm) Phenolic diaphragm compression driver, one 2" (5.08cm) Phenolic diaphragm compression driver and one 15" Fiber-composite cone /folded horn-loaded
Weight	175.5 lbs. (79.7kg)
Height	38.5" (97.8cm)
Width	24.25" (61.6cm)
Depth	25.25" (64.1cm)
Finish	Walnut, Cherry or Black Lacquer wood veneer

MSRP
\$3000 EA

Shipping quantity: Single
Shipping weight: 187.5 lbs.
UPC Code: 743878017632 (Walnut)
UPC Code: 743878017649 (Cherry)
UPC Code: 743878017625 (Black)

Cornwall III



Frequency Response	34Hz-20kHz ± 3dB
Sensitivity	102dB @ 2.83V/1meter
Impedance	8 ohms compatible
Power Handling	100 watts max continuous (400 watts peak)
Crossover	HF: 5000Hz MF: 800Hz
Drive Components	Three-way system using one 1" (2.54cm) Titanium diaphragm compression driver, one 1.75" (3.81cm) Titanium diaphragm compression driver and one 15" (38.1cm) Fiber composite cone
Weight	98 lbs. (44.5kg)
Height	35.75" (90.81cm)
Width	25.31" (64.29cm)
Depth	15.5" (39.37cm)
Finish	Walnut, Cherry or Black Lacquer wood veneer

MSRP
\$1875 EA

Shipping quantity: Single
Shipping weight: 105 lbs.
UPC Code: 743878018288 (Walnut)
UPC Code: 743878018271 (Cherry)
UPC Code: 743878018264 (Black)

Heresy III



Frequency Response	58Hz-20kHz ± 3dB
Sensitivity	99db @ 2.83V/1meter
Impedance	8 ohms compatible
Power Handling	100 watts max continuous (400 watts peak)
Crossover	HF: 5000Hz MF: 850Hz
Drive Components	Three-way system using one 1" (2.54cm) Titanium diaphragm compression driver, one 1.75" (3.81cm) Titanium diaphragm compression driver and one 12" (30.48cm) Fiber composite cone
Weight	44 lbs. (20kg)
Height	23.8" (60.5cm)
Width	15.5" (39.37cm)
Depth	13.25" (33.66cm)
Finish	Walnut, Cherry or Black Lacquer wood veneer

MSRP
\$800 EA

Shipping quantity: Single
Shipping weight: 47 lbs.
UPC Code: 743878017601 (Walnut)
UPC Code: 743878017618 (Cherry)
UPC Code: 743878017595 (Black)

Image

X10



Frequency Response	5Hz - 19kHz
Sensitivity	110 dB SPL/mW (1mW)
Impedance	50 ohms
Drive components	Full Range KG 926
Enclosure material	Aluminum body; 50" vinyl cable
Input connections	3.5mm
Dimensions	Packaging: 7.25" H x 5" W x 3.5" D
Weight	0.353 oz., 10 grams
Accessories	Faux-leather carrying case and compact pouch; 1/4-inch adaptor; airline adaptor; five sets of ear gels; ear gel cleaning tool
Finish	Anodized copper

MSRP
\$349 EA

Shipping quantity: Single
UPC Code: 743878019544

X5



Frequency Response	10Hz - 19kHz
Sensitivity	115 dB SPL/mW (1mW)
Impedance	50 ohms @ 1kHz
Drive components	Balanced Full Range Driver KG 623
Woofer	Tuned Bass Reflex Woofer System
Enclosure material	Aluminum body; 50" vinyl cable
Input connections	3.5mm
Dimensions	Packaging: 7.25" H x 5" W x 3.5" D
Weight	0.398 oz., 11.3 grams
Accessories	Five sets of different-sized ear gels; premium carrying pouch; ear gel cleaning Tool; airline adaptor

MSRP
\$249 EA

Shipping quantity: Single
UPC Code: 743878020359

Finish Anodized copper

Custom

Custom 3 |



Frequency Response	8Hz - 19kHz
Sensitivity	115 dB SPL/mW (1mW)
Impedance	32 ohms
Crossover	1500 Hz
Tweeter	KG723
Woofer	KG731
Input Connections	3.5mm
Dimensions	Packaging: 7.25" H x 5" W x 3.5" D
Weight	0.458 oz., 13 grams
Accessories	Vinyl carrying case (fits 80G iPod) 1/4" jack adaptor; airplane adaptor; five sets of ear gels; ear tip cleaning tool
Features	50" cable; Soft dark gray oval silicon ear tips
Finish	Black soft-feel paint with copper accents

MSRP
\$299 EA

Shipping quantity: Single
UPC Code: 743878019537

Custom 2 |



Frequency Response	10Hz - 19kHz
Sensitivity	112 dB SPL/mW (1mW)
Impedance	16 ohms
Drive components	Full Range KG 534 dual-balanced armatures
Input connections	3.5mm
Dimensions	Packaging: 7.25" H x 5" W x 3.5" D
Weight	0.458 oz., 13 grams
Accessories	Vinyl carrying case (fits 80G iPod); airplane adaptor; five sets of ear gels; ear tip cleaning tool
Features	50" cable; Soft dark gray oval silicon ear tips
Finish	Black soft-feel paint with silver accents

MSRP
\$199 EA

Shipping quantity: Single
UPC Code: 743878019520

Custom 1 |



Frequency Response	12Hz - 19kHz
Sensitivity	108 dB SPL/mW (1mW)
Impedance	30 ohms
Drive components	Full Range KG 332
Input connections	3.5mm
Dimensions	Packaging: 7.25" H x 5" W x 3.5" D
Weight	0.458 oz., 13 grams
Accessories	Vinyl carrying case; five sets of ear gels; ear tip cleaning tool
Features	50" cable; Soft dark gray oval silicon ear tips
Finish	Black soft-feel paint with off-white lettering

MSRP
\$129 EA

Shipping quantity: Single
UPC Code: 743878019513

AT-1A |



Description	Volume Control
Power Watt	50 RMS/ 150 Music / 300 Peak
Impedance	No
Frequency Range	35-20,000 Hz
Attenuation	33 dB
Positions	11
Control Knob	Rotating
Weather Proof	No
Finish	White, Ivory

MSRP
\$69 EA

AT-101 |



Description	Volume Control
Power Watt	50 RMS/ 150 Music / 300 Peak
Impedance	Yes
Frequency Range	35-20,000 Hz
Attenuation	42 dB
Positions	12
Control Knob	Rotating
Weather Proof	No
Finish	White, Ivory, Black, Almond

MSRP
\$79 EA

AT-101S |



Description	Volume Control
Power Watt	50 RMS/ 150 Music / 300 Peak
Impedance	Yes
Frequency Range	35-20,000 Hz
Attenuation	42 dB
Positions	12
Control Knob	Sliding
Weather Proof	No
Finish	White, Ivory, Black, Almond

MSRP
\$99 EA

I/O AT-101 |



Description	Volume Control
Power Watt	50 RMS/ 150 Music / 300 Peak
Impedance	No
Frequency Range	35-20,000 Hz
Attenuation	42 dB
Positions	12
Control Knob	Rotating
Weather Proof	Yes
Finish	White

MSRP
\$89 EA

CC-1F/2F/3F/4F/6F/8F |



Description	Connectors
Remarks	Blanks for up to 8 connectors
Finish	White

MSRP
\$39 EA

F-81 |



Description	Connectors
Remarks	F connector front and rear

MSRP
\$59 EA

RCA-FC |



Description	Connectors
Remarks	RCA jack on front and F connector on rear

MSRP
\$59 EA

JSS4-HP |



Description	Speaker Selector
Pairs of Speakers	4
Power Watt	50 RMS / 125 Music / 250 Peak
Dual Amp. Hook-Up	Yes
Volume controls	No
Weight	2.2 kg / 4.8 lb
Dimensions (H x W x D)	51 x 432 x 178 (mm) / 2 x 17 x 7 (in)
Finish	Black

MSRP
\$299 EA

JSS6-HP |



Description	Speaker Selector
Pairs of Speakers	6
Power Watt	50 RMS / 125 Music / 250 Peak
Dual Amp. Hook-Up	Yes
Volume controls	No
Weight	2.4 kg / 5.2 lb
Dimensions (H x W x D)	51 x 432 x 178 (mm) / 2 x 17 x 7 (in)
Finish	Black

MSRP
\$359 EA

JSS4-VC2 |



Description	Speaker Selector
Pairs of Speakers	4
Power Watt	50 RMS / 150 Music / 300 Peak
Dual Amp. Hook-Up	Yes
Volume controls	Yes
Weight	3.5 kg / 7.8 lb
Dimensions (H x W x D)	51 x 432 x 203 (mm) / 2 x 17 x 8 (in)
Finish	Black

MSRP
\$499 EA

JSS6-VC2 |



Description	Speaker Selector
Pairs of Speakers	6
Power Watt	50 RMS / 150 Music / 300 Peak
Dual Amp. Hook-Up	Yes
Volume controls	Yes
Weight	4.2 kg / 9.3 lb
Dimensions (H x W x D)	51 x 432 x 203 (mm) / 2 x 17 x 8 (in)
Finish	Black

MSRP
\$599 EA

ZI-8 |



Description	Impedance Strip
Remarks	Connects up to eight pairs of speakers to one receiver/ amplifier and maintains 4 ohm minimum to the amplifier. Power long/short term 75/125. Min. 4ohm.
Finish	Black

MSRP
\$149 EA

BN-1 |



Description	Banana Plug
-------------	-------------

MSRP
\$17 EA

R-100 |



Description	IR Sensor, In wall decora design
Plasma resistant	No
Remarks/Mounting	1-gang P-ring or electrical box 2 1/2" deep

MSRP
\$99 EA

R-300 |



Description	IR Sensor
Plasma resistant	No
Remarks/Mounting	1/2" hole
Finish	White, Brass

MSRP
\$129 EA

R-401 |



Description	IR Sensor
Plasma resistant	Yes
Remarks/Mounting	3/4" hole
Finish	Brass

MSRP
\$299 EA

JHL-10 |



Description	IR Sensor
Plasma resistant	No
Remarks/Mounting	Table-top
Finish	Black

MSRP
\$69 EA

IF3		Description	IR Emitter	MSRP \$15 EA
		Emitters	1	

IF4		Description	IR Emitter	MSRP \$17 EA
		Emitters	2	

IF5		Description	IR Emitter	MSRP \$15 EA
		Emitters	1	
		Remarks	Visible light	

JCB4		Description	IR Connecting Block	MSRP \$89 EA
		Emitters ports	1	

JCB41		Description	IR Connecting Block	MSRP \$89 EA
		Emitters ports	10	
		Remarks	No loss	

PS1		Description	Power Supply	MSRP \$18 EA
		Remarks	To be use with connecting blocks	

IR-1		Description	Hidden Link System	MSRP \$169 EA
		Remarks	Includes JHL-10, JCB4, 2xIF4 and PS1	
		Finish	Black	

POWER DETAIL EMOTION™

3502 Woodview Trace Indianapolis IN 46268 · 1-800-KLIPSCH®
klipsch.com